

Agriculture Hook (TCSH046)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size(kg)	W.L.L (t)	Dimension (mm)				N.W. (kg/pc)
		Φ	B	E	L	
50	0.4	8.5	34	13	56	0.04
60	0.6	9.5	41	16	70	0.06
70	1.0	11	45.5	13	80	0.095
80	1.2	11	54	17	90	0.13
90	1.8	12.5	58	18	102	0.196
100	2.4	12.5	62	19	114.5	0.3
120	2.8	15.5	62	20	118	0.33





Twin Clevis Link (TCSH048)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (t)	B.L (t)	Dimension (mm)				N.W. (kg/pc)
			A	B	K	L	
1/4-5/16	2.1	8.4	10	28	32	65	0.21
3/8	3	12	12	34	40.5	78	0.348
1/2-7/16	5.1	20.4	15	45	54	100.5	0.762
5/8	7.48	29.9	20	56	66	125.5	1.05





G80 Bolt Type Chain Shackle (TCSH049)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (t)	B.L (t)	Dimension (mm)				N.W. (kg/pc)
			A	B	D	L	
7/8-8	2	8	15	32	8.5	56	0.11
10-8	3.15	12.6	21	43	10.5	71	0.22
13-8	5.3	21.2	25	51	13	90	0.38
16-8	8	32	30	63	16.5	111	0.73





G70 Alloy Clevis Lug Link (TCSH057)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (t)	B.L (t)	Dimension (mm)					N.W. (kg/pc)
			B	A	D	K	L	
8mm	3.8	7.6	35	12	86	108	142	0.53
10mm	6.0	12	36	13.5	95	119	156	0.63
13mm	9.0	18	48.5	18	100	132	175	0.93





G80 Eye Screw (TCSH054)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (t)		Dimension (mm)				N.W. (kg/pc)
	0°	90°	D	K	Φ	L	
M6	0.4	0.15	28	13	16	42	0.05
M8	1	0.4	36	15	20	51	0.06
M10	1	0.4	45	18	25	63	0.11
M12	2	0.75	54	22	30	75	0.18
M16	4	1.5	63	28	35	88	0.28
M20	6	2.3	72	30	40	101	0.45
M24	8	3.2	90	38	50	128	0.87
M30	12	4.5	108	45	60	154	1.66
M36	16	7	126	55	70	183	2.65
M42	24	9	144	65	80	212	4.03
M48	32	12	166	70	90	238	6.38





G80 Eye Nut (TCSH055)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (t)		Dimension (mm)			N.W. (kg/pc)
	0°	90°	D	Φ	L	
M6	0.4	0.15	36	20	36	0.049
M8	1	0.4	36	20	36	0.05
M10	1	0.4	45	25	45	0.09
M12	2	0.75	54	30	53	0.16
M16	4	1.5	63	35	62	0.24
M20	6	2.3	72	40	71	0.36
M24	8	3.2	90	50	90	0.72
M30	12	4.5	108	60	109	1.32
M36	16	7	126	70	128	2.08
M42	24	9	144	80	147	3.11
M48	32	12	166	90	168	5.02





Eye Bend Hook (TCSH063)

- Powder coated, different color is available as per request.
- Working load limit permanently shown on the body.
- Max proof load is 2.5 times of the working load limited.
- Min. Breaking strength is 4 times of the W.L.L.

Size	W.L.L (t)	B.L (t)	Dimension (mm)					N.W. (kg/pc)
			A	B	E	L	H	
1.86T	1.86	7.44	13	57	15	100	18.5	0.4
2T	2	8	13	58	10	105	20	0.5
5T	5	20	20	92.5	16	170	30	1.7